



Kingston Paints Pty Ltd
ACN 067 493 065 ABN 94 067 493 065
(PO Box 327, Somerton, Vic., 3062)
33-35 Adrian Road
CAMPBELLFIELD, VIC., 3061
Ph: (03) 9357 9396
Fax: (03) 9357 9398

MATERIAL SAFETY DATA SHEET
Health, Safety & Environment Data

CURRENT AS AT: January 2014
Page 1 of 3

IDENTIFICATION

Hazardous according to criteria of Worksafe Australia

Product Name:	Spray Stain	UN Number:	1263
		Hazchem Code:	3(Y)
		Dangerous Goods Class	3
Other Names:	Paint	Subsidiary Risk Class:	None Allocated
		Poisons Schedule:	6
		Packaging Group:	II

Product Code: 515

Use: Stain to be applied usually by spray to timber.

Physical Description/Properties

Appearance:	Coloured mobile liquid with strong chemical odour
Specific Gravity:	0.86 – 0.87
Boiling Point/Range (oc):	79 – 143
Vapour Pressure:	3 kpa
Flash Point (oc):	approx 16 Abel
Flammability Limit:	LEL 1.0 UEL 11.5
Solubility in water:	110 gm/L

<u>Hazardous Ingredients:</u>	<u>CAS No:</u>	<u>Percent by weight</u>
-------------------------------	----------------	--------------------------

Pigments:

Resin:

Solvents:	Methyl Ethyl Ketone	78-93-3	10 – 30
	Xylene	1330-200-7	30 – 60

Others:

HEALTH HAZARD INFORMATION

Health Effects:**ACUTE:**

Swallowed	May cause irritation to mouth, throat and digestive tract. May cause nausea and vomiting. Large dose may cause unconsciousness.
Eye	Irritant
Skin	Irritant
Inhaled	Vapour is irritant to mucous membranes and respiratory tract. Vapours can affect the central nervous system and result in headaches and dizziness. High concentrations of vapours, if exposure is prolonged may cause unconsciousness. Aspiration of liquid into the lungs can cause serious (even fatal) pneumonitis.

FIRST AID

Swallowed	If poisoning occurs, contact a Doctor or Poisons Information Centre. If swallowed, do not induce vomiting, give a glass of water. If any suspicion of aspiration of liquid into the lungs (e.g. During vomiting) obtain medical advice immediately.
Eye	Irrigate with copious quantities of water. Seek medical attention immediately.
Skin	If skin contact occurs, remove and launder contaminated clothing and wash skin thoroughly.
Inhalation	Move to fresh air, keep warm and at rest. Seek medical attention. Remove from contaminated area. Apply artificial respiration if not breathing.
Advice to Doctor	Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS OF USE

Exposure Limits	Not established for mixture. Ingredients: Methyl Ethyl Ketone – 445 mg/m ³ , 155 ppm, Xylene 350mg/m ³ , 80 ppm TWA
Engineering Controls	Avoid breathing vapour. Local exhaust ventilation usually required. Ensure ventilation is adequate to maintain air concentration below exposure standards.

Personal Protection	Avoid eye and skin contact. Wear chemical goggles. Wear chemical resistant gloves. Wear protective clothing as necessary to avoid skin contact. Wear supplied air breathing apparatus in confined areas. Avoid prolonged or repeated skin contact.
Flammability	Avoid heat and sources of ignition. Prevent build-up of flammable vapours. Hoses should be electrically continuous and containers bonded to avoid static charge build-up.

SAFE HANDLING INFORMATION

Storage & Transport	Avoid contact with strong oxidizing agents. Store in a cool well ventilated area away from heat and ignition sources. Containers should always be kept closed in storage and properly labeled. Do not store in a low or enclosed area where vapours may become trapped. Store only in original or approved containers. This material is classified as Dangerous Goods Class 3 and must be stored and transported in accordance with State and Territory dangerous goods legislation. Shipping Name: THINNER UN 1263 PG II.
Spills & Disposal	Extinguish all ignition sources and ventilate area. For major spills, dam and recover. Prevent entry into drainage systems, rivers, etc. Collect with absorbent material such as sand, earth or sawdust. Advise authorities. Ensure waste disposal conforms with local waste disposal regulations. After recovery and evaporation, remaining soil may be disposed of to approved landfill, or if approved, allowed to degrade insitu.
Fire/Explosion Hazard	Flammable liquid. Combustion products include oxides of carbon. Vapour/air mixtures may ignite explosively. Flashback along vapour trail may occur. Use foam, CO2 powder or BCF fire extinguishers.

OTHER INFORMATION

Toxicology	Xylene – Oral LD50 (rat) 4300 mg/kg Methyl Ethyl Ketone – Oral LD50 (rat) 2737 mg/kg
------------	---

Contact Point: KINGSTON PAINTS PTY LTD
33 – 35 ADRIAN ROAD
CAMPBELLFIELD VIC 3061

(03) 9357 9396
EMERGENCY TELEPHONE NUMBER NOT AVAILABLE

This information is furnished without warranty, representation, inducement or licence of any kind except that it is accurate to the best of Kingston Paints Pty Ltd's knowledge or obtained by Kingston Paints Pty Ltd from sources believed by it to be accurate and Kingston Paints Pty Ltd does not assume any legal responsibility for use of reliance upon the same. Customers are encouraged to conduct their own tests. This information is non-controlled. It is the responsibility of the user to ensure that the issue is current.

