



Kingston Paints Pty Ltd
ACN 067 493 065 ABN 94 067 493 065
(PO Box 327, Somerton, Vic., 3062)
33-35 Adrian Road
CAMPBELLFIELD, VIC., 3061
Ph: (03) 9357 9396
Fax: (03) 9357 9398

MATERIAL SAFETY DATA SHEET
Health, Safety and Environment Data.

CURRENT AS AT: January 2014
Page 1 of 3

IDENTIFICATION

Classified as hazardous according to criteria of Worksafe Australia.

Product Name: HI LUSTRE SILVER	UN Number:	1263
	Hazchem Code:	3(Y)
	Dangerous Goods Class:	3
Other Names: PAINT	Subsidiary Risk Class:	N.A.
	Poisons Schedule:	5
	Packaging Group	III

Product Code: 105 - 6033

Use: Aluminium based coating for both Industrial and Domestic use wherever a bright silver finish is required.

Physical Description/Properties

Appearance:	Silver liquid with petroleum solvent odour.
Specific Gravity:	0.96
Boiling Point/Range (°C):	145 - 200
Vapour Pressure:	0.7 kPa
Flash Point (°C):	33 Abel
Flammability Limits (%):	LEL 0.9 UEL 5.5
Solubility in water:	Negligible.

<u>Hazardous Ingredients:</u>	<u>CAS No.</u>	<u>Percent by weight</u>
Pigments:		
Resin:		
Solvents: Mineral Turpentine	64742 – 95 – 6	30 - 60

Others: Ingredients not considered hazardous to 100%.

HEALTH HAZARD INFORMATION

HEALTH EFFECTS**ACUTE**

<u>Swallowed</u>	May cause irritation to mouth, throat and digestive tract. Large dose may cause drowsiness and may lead to unconsciousness.
<u>Eye</u>	Irritant.
<u>Skin</u>	Irritant. Avoid prolonged or repeated contact as may cause dermatitis.
<u>Inhaled</u>	Vapour is irritant to mucous membranes and respiratory tract. Vapours can affect central nervous system and result in headaches and dizziness. High concentrations of vapours, if exposure is prolonged, may cause unconsciousness. Aspiration of liquid into the lungs can cause serious (even fatal) pneumonitis.

FIRST AID

<u>Swallowed</u>	If poisoning occurs, contact a Doctor or Poisons Information Centre. If swallowed, do not induce vomiting. Give a glass of water. If any suspicion of aspiration into the lungs (e.g. during vomiting) obtain medical advice immediately.
<u>Eye</u>	Irrigate with copious quantities of water. If soreness or redness persists, seek medical attention.
<u>Skin</u>	Wash off with soap and water. Remove contaminated clothing and launder before re-use.
<u>Inhalation</u>	Move to fresh air, keep warm and at rest. Seek medical attention.
<u>Advice to Doctor</u>	Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

<u>Exposure Limits</u>	Mineral Turpentine 480 mg/m ³ , 320 ppm 8 hour time weighted average.
<u>Engineering Controls</u>	Avoid breathing vapour. Use in a well ventilated area. Local exhaust ventilation usually required.
<u>Personal Protection</u>	Avoid eye and skin contact. Wear chemical goggles. Wear chemical resistant gloves. Wear protective clothing as necessary to avoid skin contact. Wear supplied air breathing apparatus in confined areas. Avoid prolonged or repeated skin contact. Wash thoroughly after handling.
<u>Flammability</u>	This material contains flammable solvents and must be kept away from all sources of ignition (open flames, sparks, pilot lights, furnaces, spark producing switches, etc). Use only in a well ventilated area and do not smoke. Keep containers closed when not in use.
<u>Application</u>	Do not use in confined areas without supplied air breathing apparatus.

SAFE HANDLING INFORMATION

Storage and Transport

Store in a cool and well ventilated area away from all sources of heat and ignition. Store only in original containers and ensure that all containers are correctly sealed. Store and Transport in accordance with State and Territory Regulations for Class 3 Dangerous Goods.
SHIPPING NAME UN 1263 PAINT PG III

Spills and Disposal

Remove all sources of ignition and ventilate area. Absorb with inert material such as vermiculite or sand and place in a closed container. Dispose in accordance with applicable regulations.

Fire/Explosion Hazard

Flammable liquid. Vapour and air mixtures may ignite explosively. Combustion products include oxides of carbon, smoke. Use foam, carbon dioxide or dry chemical fire extinguishers. Hazchem Code 3(Y).

OTHER INFORMATION

Toxicology

No specific information available.

CONTACT POINT

KINGSTON PAINTS
33 – 35 ADRIAN ROAD
CAMPBELLFIELD VIC 3061

(03) 9357 9396
EMERGENCY TELEPHONE NUMBER NOT AVAILABLE.

upon the same. Customers are encouraged to conduct their own tests. This information is non-controlled. It is the responsibility of the user to ensure that the issue is current.