



Kingston Paints Pty Ltd
ACN 067 493 065 ABN 94 067 493 065
(PO Box 327, Somerton, Vic., 3062)
33-35 Adrian Road
CAMPBELLFIELD, VIC., 3061
Ph: (03) 9357 9396
Fax: (03) 9357 9398

MATERIAL SAFETY DATA SHEET
Health, Safety & Environment Data

CURRENT AS AT: January 2014
Page 1 of 3

IDENTIFICATION

Hazardous according to criteria of Worksafe Australia

PRODUCT NAME: PIGMENTED WIPING STAIN (PWS)	UN Number: 1263	
	Hazchem Code:	3 (Y) E
	Dangerous Goods Class	3
	Subsidiary Risk Class	None
	Poisons Schedule:	5
OTHER NAMES: Paint	Packaging Group:	III
PRODUCT CODE: 510 – Plus 4 digit No: (denotes colour)		
USE: Soluble dye for staining of interior timber furniture.		

PHYSICAL DESCRIPTION/PROPERTIES

Appearance:	High viscosity coloured liquid with strong chemical solvent odour.
Specific Gravity:	1.1 – 1.4
Flast Point (oC):	Above 23 (°C)
Flammability Limits (%):	Approx 60%
Solubility in Water:	None

HAZARDOUS INGREDIENTS: CAS NO: PERCENT BY WEIGHT:

Pigments:

Resin:

Solvents:	Xylene	10 - 30
	Petroleum Distillate	10 - 30

Others: Other ingredients not considered hazardous to 100%

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

ACUTE:

- Swallowed: May cause irritation to mouth, throat and digestive tract. May cause severe gastrointestinal irritation.
- Eye: Irritant.
- Skin: Mild irritation after prolonged or repeated contact.
- Inhaled: Vapour is irritant to mucous membranes and respiratory tract. Vapours can affect the central nervous system and result in headaches and dizziness. High concentrations of vapours, if exposure if prolonged may cause unconsciousness.

FIRST AID:

- Swallowed: If swallowed, contact a Doctor or Poisons information centre immediately. Do not induce vomiting due to risk of aspiration. Wash mouth out with water, seek medical attention.
- Eye: Wash with water for at least 15 minutes and seek medical attention.
- Skin: Remove with cloth wet with a minimum of Pigmented Wiping Stain remover. Wash residue off with soap and water. Remove contaminated clothing and launder before re-use.
- Inhalation: Move to fresh air. Keep warm and at rest. Seek medical attention. Remove from contaminated area. Apply artificial respiration if not breathing.
- Advice to Doctor: Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

- EXPOSURE LIMITS: Not established for mixture.
- ENGINEERING CONTROLS: Avoid breathing vapour and use in a well-ventilated area. Local exhaust ventilation required.
- PERSONAL PROTECTION: Avoid eye and skin contact. Wear chemical goggles and chemical resistant gloves. Wear protective clothing as necessary to avoid skin contact. Avoid prolonged or repeated skin contact. Wash thoroughly after handling.
- FLAMMABILITY: This material contains flammable solvents and must be kept away from all sources of heat and ignition (open flames, sparks, pilot lights, furnaces, spark producing switches, etc). Use only in a well-ventilated area and do not smoke. Keep containers closed when not in use.
- APPLICATION: This product is designed for wiping application. Use 500-0109 Pigmented Wiping Stain Reducer to reduce up to 50% to achieve desired finish.

SAFE HANDLING INFORMATION

- STORAGE & TRANSPORT:** Store in a cool and well-ventilated area away from all sources of heat and ignition. Avoid contact with strong oxidising agents. Store only in original or approved containers. Containers should always be kept closed in storage and properly labelled.
- SPILLS & DISPOSAL:** Extinguish all ignition sources and ventilate area. For major spills, dam and recover. Prevent entry into drainage systems, rivers etc. Collect with absorbent material such as sand (sawdust should not be used). Ensure waste disposal conforms with local waste disposal regulation. After recovery remaining soil may be disposed of to approved landfill, or if approved, allowed to degrade insitu. Rags contaminated with material should be kept in a closed container under water.
- FIRE/EXPLOSION HAZARD:** Highly flammable liquid. Use foam CO2 powder or BCF fire extinguishers. Combustion products include oxides of carbon. Vapour and air mixtures may ignite explosively. Flash back along vapour trail may occur.

OTHER INFORMATION

- TOXICOLOGY:** Not established for mixture.
- CONTACT POINT:** KINGSTON PAINTS PTY LTD
33 – 35 ADRIAN ROAD
CAMPBELLFIELD VIC 3061

(03) 9357 9396
Emergency Telephone Number Not Available.

This information is furnished without warranty, representation, inducement or licence of any kind except that it is Accurate to the best of Kingston Paints Pty Ltd's knowledge or obtained by Kingston Paints Pty Ltd from sources believed by it to be accurate and Kingston Paints Pty Ltd does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests. This information is Non-controlled. It is the responsibility of the user to ensure that the issue is current.

