

ULTRAGUARD LOW SHEEN COLOURS AND BASES

Not Classified as Hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

KINGSTON PAINTS PTY. LTD.

33 – 35 ADRIAN ROAD CAMPBELLFIELD 3061. VICTORIA A.C.N. 067 493 065

Telephone Within Australia {03} 9357 9396 International +613 9357 9396

Emergency Within Australia {03} 9357 9396 International +613 9357 9396

Facsimile Within Australia {03} 9357 9398 International +613 9357 9398

IDENTIFICATION

| | |
|-----------------------------------|--|
| Product Name : | ULTRAGUARD LOW SHEEN - COLOUR and BASES {Lead Free} |
| Proper Shipping Name | Not Required |
| UN Number | Not Required |
| Dangerous Goods Class | Not Required |
| HAZCHEM | Not Required |
| Packaging Group | Not Required |
| Initial Emergency Response | Not Required |
| Poison Schedule Number | Not Required |
| Product Use | Southern Cross Ultraguard Low Sheen is a water based, acrylic resin coating, which may be applied by brush, roller or spray. It is used as a decorative finish for painting of exterior masonry, brick, galvanized iron and timber surfaces. <u>Note</u> Bases must be tinted with Universal Colourants prior to application. |

PHYSICAL DESCRIPTION AND OTHER PROPERTIES

| | |
|-------------------------------|----------------------------------|
| Appearance | Coloured liquid |
| Initial Boiling Point: | 100 ° Celsius {Literature value} |
| Vapour Pressure: | Less than 1 |
| Specific Gravity: | 1.1 - 1.2, {depending on colour} |
| Flash Point: | Non Flammable |
| Flammability Limits | Not Required |
| Solubility in Water: | Miscible |
| pH | 8 - 10 {undiluted} |

INGREDIENTS

| CHEMICAL/SUBSTANCE NAME | CAS Number | Proportion |
|-------------------------------------|-------------------|-------------------|
| Water | 7732-18-5 | 30 - 60 % w/w |
| Coloured Pigments {Non - Hazardous} | Not Known | 10 - 30 % w/w |
| Synthetic Resin {Non - Hazardous} | Not Known | 10 - 30 % w/w |
| Additives {Non - Hazardous} | Not Known | 0 - 5 % w/w |

Material Safety Data Sheet

Page 2 of 2

ULTRAGUARD LOW SHEEN COLOURS AND BASES

Not Classified as Hazardous according to criteria of Worksafe Australia

HEALTH HAZARD INFORMATION

HEALTH EFFECTS - ACUTE

Swallowed May be a mild irritant to the mouth, throat, and stomach.
Eyes May be a mild irritant.
Skin May be a mild irritant.
Inhalation May be a mild irritant to nose, throat and respiratory tract.

HEALTH EFFECTS - CHRONIC

Chronic Not known for this product

FIRST AID

Swallowed If swallowed, give 2 glasses of water to drink.
Eyes If splashed into eyes, irrigate copiously with water for at least 15 minutes.
Skin If skin contact occurs, wash thoroughly with soap and water.
Inhaled Practically non-harmful by inhalation.
First Aid Facilities Clean Water Supply, Barrier Cream, Soap and Eye Wash Stations.
Advice to Doctor No specific treatment is recommended

PRECAUTIONS FOR USE

ENGINEERING REQUIREMENTS

Exposure Standards Not required since this product is non-hazardous as defined by the relevant Worksafe - NOHSC documents.
Engineering Controls Since this product is used on exterior surfaces, no special ventilation requirements are necessary.

PERSONAL PROTECTION

Clothing It is advisable to wear cotton overalls during the application period.
Gloves If continuous skin contact is likely to occur, it is advisable to wear PVC or Neoprene Gloves.
Eyes If splashing is likely to occur, it is advisable to wear safety glasses fitted with side shields or chemical splash goggles.
Respiratory Equipment If the ventilation is inadequate, it is advisable to wear a Type K Class 2 respirator. {AS - NZS 1715/1716}.
Footwear It is advisable to wear safety shoes or safety boots during the application period.

PROTECTIVE EQUIPMENT

Not required since this product is non-hazardous as defined by the relevant Worksafe- NOHSC documents. It is advisable to wear the recommended personal protection equipment as described in this Material Safety Data Sheet.

FLAMMABILITY

Non-Flammable. Will not burn if involved in a fire..

Material Safety Data Sheet

Page 3 of 3

ULTRAGUARD LOW SHEEN COLOURS AND BASES

Not Classified as Hazardous according to criteria of Worksafe Australia

SAFE HANDLING INFORMATION

STORAGE AND TRANSPORT

Storage Requirements Containers should be clearly labelled, rigid, strong and stored upright in a cool, dry, well ventilated area.

Transport Requirements Deemed as a Non - Dangerous Goods in accordance with the current edition "Australian Code for the Transport of Dangerous Goods by Road and Rail".

SPILLS AND DISPOSAL

Spills For all spills absorb onto sand, earth, or sawdust to absorb all spillages. Wash remaining residues with detergent and excess water.

Disposal Keep unwanted paint and residues in labelled and sealed containers for disposal via special waste collection services.

OTHER INFORMATION

WORKSAFE CLASSIFICATION

Hazard Category Not classified as a Hazardous Substance according to criteria of Worksafe Australia

CONTACT

For further information, please contact KINGSTON PAINTS PTY LTD
B.H. {03} 9357 9396
A.H. {03} 5426 4333

DISCLAIMER

This information is based on data believed by KINGSTON PAINTS PTY.LTD. to be accurate at the time of writing, but is subject to change without notice. It is given good faith, but no warranty expressed or implied is made as to its accuracy, completeness or otherwise. Every person dealing with the material referred to herein does so at their own risk, absolutely, and must make independent determination of suitability and completeness of all information from all sources to ensure there proper use.