



Kingston Paints Pty Ltd
ACN 067 493 065 ABN 94 067 493 065
(PO Box 327, Somerton, Vic., 3062)
33-35 Adrian Road
CAMPBELLFIELD, VIC., 3061
Ph: (03) 9357 9396
Fax: (03) 9357 9398

MATERIAL SAFETY DATA SHEET
Health, Safety & Environment Data

CURRENT AS AT: January 2014
Page 1 of 4

IDENTIFICATION

Hazardous according to criteria of Worksafe Australia

PRODUCT NAME:	VINYL ETCH PRIMER BLACK	UN Number:	1263
		Hazchem Code:	3 (Y) E
		Dangerous Goods Class	3.1
		Subsidiary Risk Class	N/A
		Poisons Schedule:	5
OTHER NAMES:	Paint, etc, flammable liquid		
PRODUCT CODE:	615-1212		
USE:	Etching primer/surfacer for ferrous and non-ferrous metals.		

PHYSICAL DESCRIPTION/PROPERTIES

Appearance:	Grey viscous liquid with chemical solvent odour
Specific Gravity:	0.90
Boiling Point/range (oC) :	Approximately 80 – 160oC
Vapour pressure:	Approximately 8 kPa
Flash Point (oC):	Approximately 5
Flammability Limits (%):	Not Known
Solubility in Water:	Approximately 100 gm/L
Percent Volatiles:	Approximately 80

<u>HAZARDOUS INGREDIENTS:</u>	<u>CAS NO:</u>	<u>PERCENT BY WEIGHT:</u>
Pigments: Zinc Chromate		< 10
Resin:		
Solvents: Alcohols		30 - 60
Ketones/Esters		10 - 30
Petroleum Hydrocarbons		10 – 30

Others:

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

Swallowed: May cause irritation to mouth, throat and digestive tract. May cause nausea and vomiting. Large amount may cause drowsiness and may lead to unconsciousness.

Eye: Irritant. May cause corneal damage.

Skin: Irritant. Avoid prolonged or repeated contact as may cause dermatitis

Inhaled: Vapour is irritant to mucous membranes and respiratory tract. Vapours can affect the central nervous system and result in headaches and dizziness. High concentrations of vapours, if exposure is prolonged, may cause unconsciousness. Aspiration of liquid into the lungs can cause serious (even fatal) pneumonitis.

FIRST AID:

Swallowed: If poisoning occurs, contact a Doctor or Poisons Information Centre. If swallowed, DO NOT induce vomiting due to risk of aspiration. Give a glass of water and seek medical attention. If any suspicion of aspiration into the lungs (e.g. during vomiting) obtain medical advice immediately.

Eye: Irrigate with copious quantities of water for at least 15 minutes. Seek medical attention.

Skin: If skin contact occurs wash off with soap and water. Remove and launder contaminated clothing before re-use.

Inhalation: Move to fresh air. Keep warm and at rest. Seek medical attention. Remove from contaminated area. Apply artificial respiration if not breathing.

Advice to Doctor: Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

EXPOSURE LIMITS: Not established for product. Recommend that 100 ppm 8 hour TWA be not exceeded.

VENTILATION: Avoid breathing vapour and use in a well-ventilated area. Local exhaust ventilation required. For spray application use a spray booth fitted with an effective filtered exhaust system complying with local regulation.

PERSONAL PROTECTION: Avoid eye and skin contact. Wear chemical goggles and chemical resistant gloves. Wear protective clothing as necessary to avoid skin contact. Wear supplied air breathing apparatus when spraying in confined and poorly ventilated areas.

FLAMMABILITY: Avoid heat and sources of ignition. Prevent build-up of flammable vapours. Hoses should be electrically continuous and containers bonded to avoid static charge build-up.

SPECIAL PROTECTION INFORMATION

WHEN APPLYING COATING:

This product is designed for spray application. Use a spray booth fitted with an effective filtered exhaust system complying with local regulations. Wear supplied air breathing apparatus when spraying and until spray mist has effectively dispersed. Comply with local regulations applicable to spray painting.

SAFE HANDLING INFORMATION

STORAGE & TRANSPORT: Store in a cool and well-ventilated area away from all sources of heat and ignition sources. Avoid contact with strong oxidizing agents. Store only in original or approved containers. Containers should always be kept closed in storage and properly labelled. This material is classified as Dangerous Goods Class 3.1. Store only in original containers and ensure that all containers are correctly sealed. Store and transport in accordance with State and Territory regulations for Class 3.1 Dangerous Goods.

SPILLS & DISPOSAL: Extinguish all ignition sources and ventilate area. For major spills, dam and recover. Prevent entry into drainage systems, rivers etc. Collect with absorbent material such as sand, earth or sawdust. Ensure waste disposal conforms with local waste disposal regulation. After recovery and evaporation remaining soil may be disposed of to approved landfill or if approved, allowed to degrade in situ.

FIRE/EXPLOSION HAZARD: Highly flammable liquid. Use foam, CO₂, powder or BCF Fire extinguishers. Combustion products include oxides of carbon. Remove sources of re-ignition. Vapour/air mixture may ignite explosively. Flashback along vapour trail may occur.

OTHER INFORMATION

CONTACT POINT:

KINGSTON PAINTS PTY LTD
33 – 35 ADRIAN ROAD
CAMPBELLFIELD VIC 3061

(03) 9357 9396

Emergency Telephone Number Not Available.

This information is furnished without warranty, representation, inducement or licence of any kind except that it is Accurate to the best of Kingston Paints Pty Ltd's knowledge or obtained by Kingston Paints Pty Ltd from sources believed by it to be accurate and Kingston Paints Pty Ltd does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests. This information is Non-controlled. It is the responsibility of the user to ensure that the issue is current.

